

Clean Living Disinfectants LLC

Orders@CleanLD.com 281-801-7310 507 Atascocita Rd. Humble TX 77396



INSTRUCTIONS

Biocide, Disinfectant. Sterilant and Sanitizing Agent

STEP 1: Make the Concentrate (500ppm)

*Concentrate Solution is not ready to use for disinfecting. Product needs to be Diluted (Step 2)

- 1. Fill a container with the directed amount of water
- 2. Tear open the packaging and remove the packet inside.
- 3. Place the packet in container with water. Close the lid and keep in a cool dark area for 2 hours. (**DO NOT USE BEFORE 2 HRS.**)
- 4. Remove packet after 2 hrs, no longer than 24 hrs (DO NO TRY TO REUSE PACKET)

STEP 2: Dilute Concentrate to make Disinfectant (100 ppm)

*This product needs to be diluted prior to use. Reference chart below for amt. of water needed

- 1. After 2 hours you can now use concentrate to make your disinfectant.
- 2. Mix 1 equal part of Selectrocide Concentrate with 4 equal parts water.
- 3. Disinfectant solution is now ready to use

	STEP 1 TO MAKE CONCENTRATE	
	SUBMERGE PACKET IN WATER Selectrocide	COVER & WAIT 2 HRS
	AMOUNT OF WATER TO USE	TIME
1G	1/2 Gal.	2 HOURS
5G	2.6 Gal.	2 HOURS
12G	6.2 Gal	2 HOURS
DO NOT EVENOUS CELECTROCIDE DICINISECTA		

STEP 2 TO MAKE DISINFECTANT		
1 PART CONCENTRATE : 4 PARTS WATER		
"Selectrocide"		
AMOUNT OF	YIELDS AMOUNT OF	
WATER	DISINFECTANT	
2 GAL	2.5 GAL	
10.6 GAL	13.2 GAL	
24.8 GAL	31 GAL	

DO NOT EXPOSE SELECTROCIDE DISINFECTANT SOLUTION TO SUNLIGHT

RECOMMENDED SPECIFICATIONS FOR CONTAINERS USED WITH PRODUCTS FOR USE IN GENERATING OR STORING ACTIVATED SOLUTIONS

The container should be—or be comparable to, an UN-approved, liquid-resealable containment incorporating a gasket-sealing surface and locking mechanism. Construction should be of dark or opaque/UV-blocking (preferred) oxidation-resistant plastic or glass. Some materials recommended include:

- High Density Polyethylene (HDPE)
- Polypropylene (PP)
- Polyethylene Terephthalate (PET) (PETE)
- Polyvinyl Chloride (PVC)
- Polycarbonate (PC)
- Glass (UV-blocking preferred)
- Gasket materials; silicone, viton or EPDM

