

Material Safety Data Sheet

DOW AGROSCIENCES LLC

Product name: CROSSBOW™ Herbicide

Issue Date: 12/05/2014

Print Date: 12/05/2014

DOW AGROSCIENCES LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: CROSSBOW™ Herbicide

COMPANY IDENTIFICATION

DOW AGROSCIENCES LLC
9330 ZIONSVILLE RD
INDIANAPOLIS IN 46268-1053
UNITED STATES

Customer Information Number:

800-992-5994

info@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 800-992-5994

Local Emergency Contact: 352-323-3500

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance

Physical state	Liquid.
Color	Red to brown

Odor

Sweet

Hazard Summary	
	<u>DANGER!!</u> Combustible liquid and vapor. May cause allergic skin reaction. May cause eye irritation. May cause skin irritation. May cause respiratory tract irritation. Harmful or fatal if swallowed; can enter lungs and cause damage. Isolate area. Keep upwind of spill. Toxic fumes may be released in fire situations.

Potential Health Effects

Ingestion: Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

Inhalation: Prolonged excessive exposure to mist may cause adverse effects.
Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.
Observations in animals include:
Lethargy.

Skin: Skin contact may cause an allergic skin reaction.

Skin: Prolonged skin contact is unlikely to result in absorption of harmful amounts.
Observations in animals include:
Lethargy.

Skin: Brief contact is essentially nonirritating to skin.
Prolonged contact may cause moderate skin irritation with local redness.
May cause drying and flaking of the skin.

Ingestion: Low toxicity if swallowed.
Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.
Observations in animals include:
Lethargy.
In humans, symptoms may include:
Abdominal discomfort.
May cause central nervous system depression.
Diarrhea.

Eyes: May cause moderate eye irritation.
Corneal injury is unlikely.

Chronic Exposure: For similar active ingredient(s).
2,4-Dichlorophenoxyacetic acid.
In laboratory animals, excessive doses toxic to the parent animals caused decreased weight and survival of offspring.
For the active ingredient(s):
Has been toxic to the fetus in laboratory animals at doses toxic to the mother.
For the active ingredient(s):
In animals, effects have been reported on the following organs:
Kidney.
Liver.
Eye.
Thyroid.
For kerosene:
In animals, effects have been reported on the following organs after exposure to aerosols:
Central nervous system.
Respiratory tract.
Observations in animals include:
Anesthetic or narcotic effects.
Contains component(s) which have been reported to cause effects on the following organs in animals:
Blood.
Spleen.
For the minor component(s):
Has caused birth defects in laboratory animals only at doses toxic to the mother.

Has been toxic to the fetus in laboratory animals at doses toxic to the mother.
 These concentrations exceed relevant human dose levels.
 For similar active ingredient(s).

Triclopyr.

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

For the solvent(s):

In a lifetime animal dermal carcinogenicity study, an increased incidence of skin tumors was observed when kerosene was applied at doses that also produced skin irritation. This response was similar to that produced in skin by other types of chronic chemical/physical irritation. No increase in tumors was observed when non-irritating dilutions of kerosene were applied at equivalent doses, indicating that kerosene is unlikely to cause skin cancer in the absence of long-term continued skin irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Component	CASRN	Concentration
2,4-Dichlorophenoxyacetic acid, butoxyethyl ester	1929-73-3	34.4%
Triclopyr-2-butoxyethyl ester	64700-56-7	16.5%
Kerosene (petroleum)	8008-20-6	41.5%
2-Ethylhexanol	104-76-7	1.9%
Balance	Not available	5.7%

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment advice. If breathing is difficult, oxygen should be administered by qualified personnel.

Skin contact: Take off contaminated clothing. Wash skin with soap and plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of properly. Suitable emergency safety shower facility should be available in work area.

Eye contact: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice. Suitable emergency eye wash facility should be available in work area.

Ingestion: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Skin contact may aggravate preexisting dermatitis. Repeated excessive exposure may aggravate preexisting lung disease. Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. The decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. Exposure to this material may impair the ability to operate hazardous equipment or drive vehicles. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control center or doctor, or going for treatment.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: no data available

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Hydrogen chloride. Carbon monoxide. Carbon dioxide. Combustion products may include trace amounts of: Phosgene.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Consider feasibility of a controlled burn to minimize environment damage. Foam fire extinguishing system is preferred because uncontrolled water can spread possible contamination. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to section 7, Handling, for additional precautionary measures. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Small spills: Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers. Large spills: Contact Dow AgroSciences for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep out of reach of children. Keep away from heat, sparks and flame. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Avoid contact with eyes, skin, and clothing. Do not swallow. Avoid breathing vapor or mist. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Store in a dry place. Store in original container. Keep container tightly closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Triclopyr-2-butoxyethyl ester	Dow IHG	TWA	2 mg/m ³
	Dow IHG	TWA	SKIN, DSEN
Kerosene (petroleum)	Dow IHG	TWA	10 mg/m ³ , as total hydrocarbon vapor
	ACGIH	TWA	200 mg/m ³ , as total hydrocarbon vapor
	ACGIH	TWA	Absorbed via skin
	OSHA Z-1	TWA	2,000 mg/m ³ 500 ppm
	OSHA P0	TWA	1,600 mg/m ³ 400 ppm

RECOMMENDATIONS IN THIS SECTION ARE FOR MANUFACTURING, COMMERCIAL BLENDING AND PACKAGING WORKERS. APPLICATORS AND HANDLERS SHOULD SEE THE PRODUCT LABEL FOR PROPER PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING.

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In misty atmospheres, use an approved particulate respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Liquid.
Color	Red to brown
Odor	Sweet
Odor Threshold	No test data available
pH	3.8 10% <i>pH Electrode</i> (10% solution in water)
Melting point/range	Not applicable
Freezing point	No test data available
Boiling point (760 mmHg)	> 175 °C (> 347 °F) (kerosene)
Flash point	closed cup 64 °C (147 °F) <i>Closed Cup</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	No test data available

Upper explosion limit	No test data available
Vapor Pressure	0.1 mmHg at 37.8 °C (100.0 °F) (kerosene)
Relative Vapor Density (air = 1)	4.7 (kerosene)
Relative Density (water = 1)	no data available
Water solubility	emulsifiable
Partition coefficient: n-octanol/water	no data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Dynamic Viscosity	6.56 mPa.s at 25 °C (77 °F)
Kinematic Viscosity	no data available
Explosive properties	No No No
Oxidizing properties	no data available
Liquid Density	1.0114 g/cm ³ at 20 °C (68 °F) <i>Digital density meter</i>
Molecular weight	no data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Some components of this product can decompose at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems.

Incompatible materials: Avoid contact with: Acids. Bases. Oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Hydrogen chloride. Nitrogen oxides. Toxic gases are released during decomposition. Decomposition products can include trace amounts of: Phosgene.

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may

cause injury. Observations in animals include: Lethargy. In humans, symptoms may include: Abdominal discomfort. May cause central nervous system depression. Diarrhea.

LD50, rat, male and female, 1,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts. Observations in animals include: Lethargy.

As product:

LD50, rabbit, male and female, > 5,000 mg/kg

Acute inhalation toxicity

Prolonged excessive exposure to mist may cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. Observations in animals include: Lethargy.

As product:

LC50, rat, male and female, 4 Hour, Aerosol, > 5.19 mg/l

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause moderate skin irritation with local redness.

May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause moderate eye irritation.

Corneal injury is unlikely.

Sensitization

Skin contact may cause an allergic skin reaction.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the active ingredient(s):

In animals, effects have been reported on the following organs:

Kidney.

Liver.

Eye.

Thyroid.

For kerosene:

In animals, effects have been reported on the following organs after exposure to aerosols:

Central nervous system.

Respiratory tract.

Observations in animals include:

Anesthetic or narcotic effects.

Contains component(s) which have been reported to cause effects on the following organs in animals:

Blood.

Spleen.

Carcinogenicity

For the solvent(s): In a lifetime animal dermal carcinogenicity study, an increased incidence of skin tumors was observed when kerosene was applied at doses that also produced skin irritation. This response was similar to that produced in skin by other types of chronic chemical/physical irritation. No increase in tumors was observed when non-irritating dilutions of kerosene were applied at equivalent doses, indicating that kerosene is unlikely to cause skin cancer in the absence of long-term continued skin irritation.

For similar active ingredient(s). Triclopyr. Did not cause cancer in laboratory animals.

For similar active ingredient(s). Various animal cancer tests have shown no reliably positive association between 2,4-D exposure and cancer. Epidemiology studies on herbicide use have been both positive and negative with the majority being negative.

Teratogenicity

For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

For the minor component(s): Has caused birth defects in laboratory animals only at doses toxic to the mother. Has been toxic to the fetus in laboratory animals at doses toxic to the mother. These concentrations exceed relevant human dose levels.

Reproductive toxicity

For similar active ingredient(s). 2,4-Dichlorophenoxyacetic acid. In laboratory animals, excessive doses toxic to the parent animals caused decreased weight and survival of offspring.

For similar active ingredient(s). Triclopyr. In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

For the active ingredient(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

Carcinogenicity

Component	List	Classification
Kerosene (petroleum)	ACGIH	A3: Confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

Toxicity

2,4-Dichlorophenoxyacetic acid, butoxyethyl ester

Acute toxicity to fish

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LC50, *Lepomis macrochirus* (Bluegill sunfish), static test, 96 Hour, 0.61 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

LC50, *Daphnia magna* (Water flea), static test, 48 Hour, 7.2 - 33 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EbC50, *Pseudokirchneriella subcapitata* (green algae), static test, 5 d, Biomass, 25 mg/l, OECD Test Guideline 201 or Equivalent

EbC50, *Lemna minor* (duckweed), static test, 5 d, Biomass, 0.576 mg/l, OECD 221.

Toxicity to Above Ground Organisms

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg).

Material is practically non-toxic to birds on a dietary basis (LC50 > 5000 ppm).

dietary LC50, *Colinus virginianus* (Bobwhite quail), > 5620mg/kg diet.

oral LD50, *Colinus virginianus* (Bobwhite quail), > 2000mg/kg bodyweight.

Triclopyr-2-butoxyethyl ester**Acute toxicity to fish**

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).

LC50, *Lepomis macrochirus* (Bluegill sunfish), flow-through test, 96 Hour, 0.36 mg/l

LC50, Fish., 96 Hour, 0.310 mg/l

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), 48 Hour, 2.9 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50, *Pseudokirchneriella subcapitata* (green algae), 96 Hour, Growth rate inhibition, > 3.00 mg/l, OECD Test Guideline 201

EbC50, diatom *Navicula* sp., 120 Hour, Biomass, 0.193 mg/l

EbC50, *Lemna gibba*, Biomass, 2.2 mg/l

Chronic toxicity to fish

NOEC, Rainbow trout (*Oncorhynchus mykiss*), 0.0263 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, *Daphnia magna* (Water flea), 21 d, number of offspring, 1.6 mg/l

LOEC, *Daphnia magna* (Water flea), 21 d, number of offspring, 5.1 mg/l

MATC (Maximum Acceptable Toxicant Level), *Daphnia magna* (Water flea), 21 d, number of offspring, 2.9 mg/l

Toxicity to Above Ground Organisms

Material is slightly toxic to birds on an acute basis (LD50 between 501 and 2000 mg/kg).

Material is slightly toxic to birds on a dietary basis (LC50 between 1001 and 5000 ppm).

oral LD50, *Colinus virginianus* (Bobwhite quail), 21 d, 735 mg/kgmg/kg bodyweight.

dietary LC50, *Colinus virginianus* (Bobwhite quail), 8 d, 1,890 mg/kgmg/kg bodyweight.

oral LD50, *Apis mellifera* (bees), 48 Hour, mortality, > 110µg/bee

contact LD50, *Apis mellifera* (bees), 48 Hour, mortality, > 100µg/bee

Toxicity to soil-dwelling organisms

LC50, *Eisenia fetida* (earthworms), 14 d, > 1,042 mg/kg

LC50, Eisenia fetida (earthworms), 14 d, > 521 mg/kg

Kerosene (petroleum)

Acute toxicity to fish

Based on information for component(s):

Material is slightly toxic to fish on an acute basis (LC50 between 10 and 100 mg/L).

2-Ethylhexanol

Acute toxicity to fish

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 32 - 37 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, 35.2 mg/l, OECD Test Guideline 202

EC50, Daphnia magna (Water flea), 48 Hour, 39 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 11.5 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, Bacteria, 16 Hour, 256 - 320 mg/l

Balance

Acute toxicity to fish

No relevant data found.

Persistence and degradability

2,4-Dichlorophenoxyacetic acid, butoxyethyl ester

Biodegradability: Chemical degradation (hydrolysis) is expected in the environment. For similar active ingredient(s). Material is expected to be readily biodegradable.

Triclopyr-2-butoxyethyl ester

Biodegradability: Chemical degradation (hydrolysis) is expected in the environment.

Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail

Biodegradation: 18 %

Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

Theoretical Oxygen Demand: 1.39 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
	0.004 mg/mg

Stability in Water (1/2-life)

Hydrolysis, half-life, 8.7 d, pH 7, Half-life Temperature 25 °C

Photodegradation**Atmospheric half-life:** 5.6 Hour**Method:** Estimated.**Kerosene (petroleum)****Biodegradability:** Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%).**Chemical Oxygen Demand:** 1.16 mg/mg Dichromate**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	31.000 %
10 d	39.700 %
20 d	58.600 %

Photodegradation**Test Type:** Half-life (indirect photolysis)**Sensitizer:** Radicaux OH**Atmospheric half-life:** 0.767 d**Method:** Estimated.**2-Ethylhexanol****Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 68 %**Exposure time:** 17 d**Method:** OECD Test Guideline 301B or Equivalent

10-day Window: Not applicable

Biodegradation: > 95 %**Exposure time:** 5 d**Method:** OECD Test Guideline 302B or Equivalent**Theoretical Oxygen Demand:** 2.95 mg/mg**Chemical Oxygen Demand:** 2.70 mg/mg**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	26 - 70 %
10 d	75 - 81 %
20 d	86 - 87 %

Photodegradation**Test Type:** Half-life (indirect photolysis)**Sensitizer:** Radicaux OH**Atmospheric half-life:** 9.7 Hour

Method: Estimated.

Balance

Biodegradability: No relevant data found.

Bioaccumulative potential

2,4-Dichlorophenoxyacetic acid, butoxyethyl ester

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 4.35 Measured

Triclopyr-2-butoxyethyl ester

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 4.62

Bioconcentration factor (BCF): 110 Fish.

Kerosene (petroleum)

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 6.1 Measured

Bioconcentration factor (BCF): 314 Fish. Estimated. **Bioconcentration factor (BCF):** 61 - 159 Fish.

2-Ethylhexanol

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.1 Measured

Balance

Bioaccumulation: No relevant data found.

Mobility in soil

2,4-Dichlorophenoxyacetic acid, butoxyethyl ester

No relevant data found.

Triclopyr-2-butoxyethyl ester

Calculation of meaningful sorption data was not possible due to very rapid degradation in the soil.

For the degradation product:

Triclopyr.

Potential for mobility in soil is very high (Koc between 0 and 50).

Kerosene (petroleum)

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient(Koc): 5900 Estimated.

2-Ethylhexanol

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient(Koc): 800 Estimated.

Balance

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Combustible liquid, n.o.s.(Kerosine (petroleum))
UN number	NA 1993
Class	CBL
Packing group	III
Reportable Quantity	2,4-D Ester

Classification for SEA transport (IMO-IMDG):

Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(2,4-D Ester, Triclopyr-2-butoxyethyl ester)
UN number	UN 3082
Class	9
Packing group	III
Marine pollutant	2,4-D Ester, Triclopyr-2-butoxyethyl ester
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.(2,4-D Ester, Triclopyr-2-butoxyethyl ester)
UN number	UN 3082
Class	9
Packing group	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Fire Hazard
Acute Health Hazard
Chronic Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**Components**

2,4-Dichlorophenoxyacetic acid, butoxyethyl ester

CASRN

1929-73-3

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Components

2,4-Dichlorophenoxyacetic acid, butoxyethyl ester

CASRN

1929-73-3

Kerosene (petroleum)

8008-20-6

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

United States TSCA Inventory (US.TSCA)

This product contains chemical substance(s) exempt from U.S. EPA TSCA Inventory requirements. It is regulated as a pesticide subject to Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) requirements.

16. OTHER INFORMATION

Hazard Rating System**NFPA**

Health	Fire	Reactivity
1	2	0

Revision

Identification Number: 101199269 / A211 / Issue Date: 12/05/2014 / Version: 4.1

DAS Code: XRM-4715

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

Absorbed via skin	Absorbed via skin
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
SKIN, DSEN	Absorbed via Skin, Skin Sensitizer
TWA	8-hour, time-weighted average

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW AGROSCIENCES LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.